

POScale SERIES Ticket Printing Scale

Commercial Scale



Pole Display Type

FEATURES

- Store up to 1799 PLU
- 8 Preset key for direct PLU
- Up to 4 different clerk sales support
- PC software management
 - PLU data up/down loading
 - Sales reporting
 - Customization of receipt format
 - Image up-loading(*.BMP)
 - Bar code setting
- RS-232C
- Cash drawer (RJ11) interface
- Rechargeable battery

OPTIONS

- Back light
- Pole type display
- Waterproof cover

SPECIFICATIONS

Model	POSCALE		
Weighing Capacity	6 kg	15 kg	30 kg
Division, e=	2g	5g	10g
Display Digit	LCD 5/6/6 (Weight / Unit price / Total price)		
Printer Information	<ul style="list-style-type: none"> • Thermal Printing, 32 Characters Per Line • Printing Speed <ul style="list-style-type: none"> - Dark 1 & AC Power : 50 mm/sec - Dark 5 & AC Power : 35 mm/sec - Dark 1 & DC(8.4V) : 44 mm/sec - Dark 5 & DC(8.4V) : 28 mm/sec • Recommended Size for Thermal Paper <ul style="list-style-type: none"> - 58 mm (Width) / 65_{μm}(Thickness) - 60 mm (Maximum Diameter) 		
Power	AC 110/220/230V, 50 / 60Hz		
Operating Temperature	-10°C ~ +40°C		
Power Utilities	PC, Cash Drawer (12 volts)		
Power Consumption	Maximum 35W		
Battery Life	<ul style="list-style-type: none"> • Rechargeable Battery (Inside) : 7.4V (Li-ion) • Battery Life (Continuous Usage) <ul style="list-style-type: none"> - Usage time EST.48 hrs 		
Dimensions(mm)	Standard Type : 375(W) × 397(D) × 128(H) Pole Type : 375(W) × 433(D) × 436(H)		
Product Weight	Standard Type : 6.8 kg Pole Type : 8 kg		